

Express Mail No. EV178016505US

PATENT APPLICATION OF
HARVEY A. RESTAINO
EDWARD J. AMATO
ENTITLED
CABLE FOR ELECTRONIC BATTERY TESTER

Docket No. C382.12-0147

CABLE FOR ELECTRONIC BATTERY TESTER

BACKGROUND OF THE INVENTION

The present invention relates to electronic battery testers of the type used to test storage batteries. More specifically, the present invention relates to cables which are used to couple such electronic battery testers to storage batteries.

Storage batteries have long been used to provide power to various types of systems such as automobiles or as standby power sources. In order to fully utilize such batteries, it is often desirable to perform a test on the battery which provides an indication related to the condition of the battery. For example, such a test can provide an indication that a battery is weak and should be replaced, or that a battery is discharged and should be charged.

Battery tests can be as simple as a visual inspection to more complex tests such as measuring the specific gravity of acid used in the battery. A simple electronic battery test can be based upon the voltage measured across the battery. Another electronic battery test is a load test in which a load is applied to the battery and the response of the battery is observed. A less intrusive way of measuring the condition of a battery is based upon a dynamic parameter of the battery. Such a measurement technique has been pioneered by Midtronics, Inc. of Willowbrook, Illinois and Dr. Keith S. Champlin as shown and described in U.S. Patent No. 3,873,911,

issued March 25, 1975, to Champlin, entitled ELECTRONIC
BATTERY TESTING DEVICE; U.S. Patent No. 3,909,708,
issued September 30, 1975, to Champlin, entitled
ELECTRONIC BATTERY TESTING DEVICE; U.S. Patent No.
5 4,816,768, issued March 28, 1989, to Champlin, entitled
ELECTRONIC BATTERY TESTING DEVICE; U.S. Patent No.
4,825,170, issued April 25, 1989, to Champlin, entitled
ELECTRONIC BATTERY TESTING DEVICE WITH AUTOMATIC
VOLTAGE SCALING; U.S. Patent No. 4,881,038, issued
10 November 14, 1989, to Champlin, entitled ELECTRONIC
BATTERY TESTING DEVICE WITH AUTOMATIC VOLTAGE SCALING
TO DETERMINE DYNAMIC CONDUCTANCE; U.S. Patent No.
4,912,416, issued March 27, 1990, to Champlin, entitled
ELECTRONIC BATTERY TESTING DEVICE WITH STATE-OF-CHARGE
15 COMPENSATION; U.S. Patent No. 5,140,269, issued August
18, 1992, to Champlin, entitled ELECTRONIC TESTER FOR
ASSESSING BATTERY/CELL CAPACITY; U.S. Patent No.
5,343,380, issued August 30, 1994, entitled METHOD AND
APPARATUS FOR SUPPRESSING TIME VARYING SIGNALS IN
20 BATTERIES UNDERGOING CHARGING OR DISCHARGING; U.S.
Patent No. 5,572,136, issued November 5, 1996, entitled
ELECTRONIC BATTERY TESTER WITH AUTOMATIC COMPENSATION
FOR LOW STATE-OF-CHARGE; U.S. Patent No. 5,574,355,
issued November 12, 1996, entitled METHOD AND APPARATUS
25 FOR DETECTION AND CONTROL OF THERMAL RUNAWAY IN A
BATTERY UNDER CHARGE; U.S. Patent No. 5,585,416, issued
December 10, 1996, entitled APPARATUS AND METHOD FOR
STEP-CHARGING BATTERIES TO OPTIMIZE CHARGE ACCEPTANCE;
U.S. Patent No. 5,585,728, issued December 17, 1996,

entitled ELECTRONIC BATTERY TESTER WITH AUTOMATIC
COMPENSATION FOR LOW STATE-OF-CHARGE; U.S. Patent No.
5,589,757, issued December 31, 1996, entitled APPARATUS
AND METHOD FOR STEP-CHARGING BATTERIES TO OPTIMIZE
5 CHARGE ACCEPTANCE; U.S. Patent No. 5,592,093, issued
January 7, 1997, entitled ELECTRONIC BATTERY TESTING
DEVICE LOOSE TERMINAL CONNECTION DETECTION VIA A
COMPARISON CIRCUIT; U.S. Patent No. 5,598,098, issued
January 28, 1997, entitled ELECTRONIC BATTERY TESTER
10 WITH VERY HIGH NOISE IMMUNITY; U.S. Patent No.
5,656,920, issued August 12, 1997, entitled METHOD FOR
OPTIMIZING THE CHARGING LEAD-ACID BATTERIES AND AN
INTERACTIVE CHARGER; U.S. Patent No. 5,757,192, issued
May 26, 1998, entitled METHOD AND APPARATUS FOR
15 DETECTING A BAD CELL IN A STORAGE BATTERY; U.S. Patent
No. 5,821,756, issued October 13, 1998, entitled
ELECTRONIC BATTERY TESTER WITH TAILORED COMPENSATION
FOR LOW STATE-OF-CHARGE; U.S. Patent No. 5,831,435,
issued November 3, 1998, entitled BATTERY TESTER FOR
20 JIS STANDARD; U.S. Patent No. 5,914,605, issued June
22, 1999, entitled ELECTRONIC BATTERY TESTER; U.S.
Patent No. 5,945,829, issued August 31, 1999, entitled
MIDPOINT BATTERY MONITORING; U.S. Patent No. 6,002,238,
issued December 14, 1999, entitled METHOD AND APPARATUS
25 FOR MEASURING COMPLEX IMPEDANCE OF CELLS AND BATTERIES;
U.S. Patent No. 6,037,751, issued March 14, 2000,
entitled APPARATUS FOR CHARGING BATTERIES; U.S. Patent
No. 6,037,777, issued March 14, 2000, entitled METHOD
AND APPARATUS FOR DETERMINING BATTERY PROPERTIES FROM

COMPLEX IMPEDANCE/ADMITTANCE; U.S. Patent No. 6,051,976, issued April 18, 2000, entitled METHOD AND APPARATUS FOR AUDITING A BATTERY TEST; U.S. Patent No. 6,081,098, issued June 27, 2000, entitled METHOD AND
5 APPARATUS FOR CHARGING A BATTERY; U.S. Patent No. 6,091,245, issued July 18, 2000, entitled METHOD AND APPARATUS FOR AUDITING A BATTERY TEST; U.S. Patent No. 6,104,167, issued August 15, 2000, entitled METHOD AND APPARATUS FOR CHARGING A BATTERY; U.S. Patent No.
10 6,137,269, issued October 24, 2000, entitled METHOD AND APPARATUS FOR ELECTRONICALLY EVALUATING THE INTERNAL TEMPERATURE OF AN ELECTROCHEMICAL CELL OR BATTERY; U.S. Patent No. 6,163,156, issued December 19, 2000, entitled ELECTRICAL CONNECTION FOR ELECTRONIC BATTERY
15 TESTER; U.S. Patent No. 6,172,483, issued January 9, 2001, entitled METHOD AND APPARATUS FOR MEASURING COMPLEX IMPEDANCE OF CELL AND BATTERIES; U.S. Patent No. 6,172,505, issued January 9, 2001, entitled ELECTRONIC BATTERY TESTER; U.S. Patent No. 6,222,369,
20 issued April 24, 2001, entitled METHOD AND APPARATUS FOR DETERMINING BATTERY PROPERTIES FROM COMPLEX IMPEDANCE/ADMITTANCE; U.S. Patent No. 6,225,808, issued May 1, 2001, entitled TEST COUNTER FOR ELECTRONIC BATTERY TESTER; U.S. Patent No. 6,249,124, issued June
25 19, 2001, entitled ELECTRONIC BATTERY TESTER WITH INTERNAL BATTERY; U.S. Patent No. 6,259,254, issued July 10, 2001, entitled APPARATUS AND METHOD FOR CARRYING OUT DIAGNOSTIC TESTS ON BATTERIES AND FOR RAPIDLY CHARGING BATTERIES; U.S. Patent No. 6,262,563,

issued July 17, 2001, entitled METHOD AND APPARATUS FOR
MEASURING COMPLEX ADMITTANCE OF CELLS AND BATTERIES;
U.S. Patent No. 6,294,896, issued September 25, 2001;
entitled METHOD AND APPARATUS FOR MEASURING COMPLEX
5 SELF-IMMITANCE OF A GENERAL ELECTRICAL ELEMENT; U.S.
Patent No. 6,294,897, issued September 25, 2001,
entitled METHOD AND APPARATUS FOR ELECTRONICALLY
EVALUATING THE INTERNAL TEMPERATURE OF AN
ELECTROCHEMICAL CELL OR BATTERY; U.S. Patent No.
10 6,304,087, issued October 16, 2001, entitled APPARATUS
FOR CALIBRATING ELECTRONIC BATTERY TESTER; U.S. Patent
No. 6,310,481, issued October 30, 2001, entitled
ELECTRONIC BATTERY TESTER; U.S. Patent No. 6,313,607,
issued November 6, 2001, entitled METHOD AND APPARATUS
15 FOR EVALUATING STORED CHARGE IN AN ELECTROCHEMICAL CELL
OR BATTERY; U.S. Patent No. 6,313,608, issued November
6, 2001, entitled METHOD AND APPARATUS FOR CHARGING A
BATTERY; U.S. Patent No. 6,316,914, issued November 13,
2001, entitled TESTING PARALLEL STRINGS OF STORAGE
20 BATTERIES; U.S. Patent No. 6,323,650, issued November
27, 2001, entitled ELECTRONIC BATTERY TESTER; U.S.
Patent No. 6,329,793, issued December 11, 2001,
entitled METHOD AND APPARATUS FOR CHARGING A BATTERY;
U.S. Patent No. 6,331,762, issued December 18, 2001,
25 entitled ENERGY MANAGEMENT SYSTEM FOR AUTOMOTIVE
VEHICLE; U.S. Patent No. 6,332,113, issued December 18,
2001, entitled ELECTRONIC BATTERY TESTER; U.S. Patent
No. 6,351,102, issued February 26, 2002, entitled
AUTOMOTIVE BATTERY CHARGING SYSTEM TESTER; U.S. Patent

No. 6,359,441, issued March 19, 2002, entitled
ELECTRONIC BATTERY TESTER; U.S. Patent No. 6,363,303,
issued March 26, 2002, entitled ALTERNATOR DIAGNOSTIC
SYSTEM, U.S. Patent No. 6,392,414, issued May 21, 2002,
5 entitled ELECTRONIC BATTERY TESTER; U.S. Patent No.
6,417,669, issued July 9, 2002, entitled SUPPRESSING
INTERFERENCE IN AC MEASUREMENTS OF CELLS, BATTERIES AND
OTHER ELECTRICAL ELEMENTS; U.S. Patent No. 6,424,158,
issued July 23, 2002, entitled APPARATUS AND METHOD FOR
10 CARRYING OUT DIAGNOSTIC TESTS ON BATTERIES AND FOR
RAPIDLY CHARGING BATTERIES; U.S. Patent No. 6,441,585,
issued August 17, 2002, entitled APPARATUS AND METHOD
FOR TESTING RECHARGEABLE ENERGY STORAGE BATTERIES; U.S.
Patent No. 6,445,158, issued September 3, 2002,
15 entitled VEHICLE ELECTRICAL SYSTEM TESTER WITH ENCODED
OUTPUT; U.S. Patent No. 6,456,045, issued September 24,
2002, entitled INTEGRATED CONDUCTANCE AND LOAD TEST
BASED ELECTRONIC BATTERY TESTER; U.S. Patent No.
6,466,025, issued October 15, 2002, entitled ALTERNATOR
20 TESTER; U.S. Patent No. 6,466,026, issued October 15,
2002, entitled PROGRAMMABLE CURRENT EXCITER FOR
MEASURING AC IMMITTANCE OF CELLS AND BATTERIES; U.S.
Serial No. 09/703,270, filed October 31, 2000, entitled
ELECTRONIC BATTERY TESTER; U.S. Serial No.
25 09/780,146, filed February 9, 2001, entitled STORAGE
BATTERY WITH INTEGRAL BATTERY TESTER; U.S. Serial No.
09/816,768, filed March 23, 2001, entitled MODULAR
BATTERY TESTER; U.S. Serial No. 09/756,638, filed
January 8, 2001, entitled METHOD AND APPARATUS FOR

DETERMINING BATTERY PROPERTIES FROM COMPLEX
IMPEDANCE/ADMITTANCE; U.S. Serial No. 09/862,783, filed
May 21, 2001, entitled METHOD AND APPARATUS FOR TESTING
CELLS AND BATTERIES EMBEDDED IN SERIES/PARALLEL
5 SYSTEMS; U.S. Serial No. 09/960,117, filed September
20, 2001, entitled IN-VEHICLE BATTERY MONITOR; U.S.
Serial No. 09/908,389, filed July 18, 2001, entitled
BATTERY CLAMP WITH INTEGRATED CIRCUIT SENSOR; U.S.
Serial No. 09/908,278, filed July 18, 2001, entitled
10 BATTERY CLAMP WITH EMBEDDED ENVIRONMENT SENSOR; U.S.
Serial No. 09/880,473, filed June 13, 2001; entitled
BATTERY TEST MODULE; U.S. Serial No. 09/940,684, filed
August 27, 2001, entitled METHOD AND APPARATUS FOR
EVALUATING STORED CHARGE IN AN ELECTROCHEMICAL CELL OR
15 BATTERY; U.S. Serial No. 60/330,441, filed October 17,
2001, entitled ELECTRONIC BATTERY TESTER WITH RELATIVE
TEST OUTPUT; U.S. Serial No. 60/348,479, filed October
29, 2001, entitled CONCEPT FOR TESTING HIGH POWER VRLA
BATTERIES; U.S. Serial No. 10/046,659, filed October
20 29, 2001, entitled ENERGY MANAGEMENT SYSTEM FOR
AUTOMOTIVE VEHICLE; U.S. Serial No. 09/993,468, filed
November 14, 2001, entitled KELVIN CONNECTOR FOR A
BATTERY POST; U.S. Serial No. 09/992,350, filed
November 26, 2001, entitled ELECTRONIC BATTERY TESTER,
25 U.S. Serial No. 60/341,902, filed December 19, 2001,
entitled BATTERY TESTER MODULE; U.S. Serial No.
10/042,451, filed January 8, 2002, entitled BATTERY
CHARGE CONTROL DEVICE, U.S. Serial No. 10/073,378,
filed February 8, 2002, entitled METHOD AND APPARATUS

USING A CIRCUIT MODEL TO EVALUATE CELL/BATTERY
PARAMETERS; U.S. Serial No. 10/093,853, filed March 7,
2002, entitled ELECTRONIC BATTERY TESTER WITH NETWORK
COMMUNICATION; U.S. Serial No. 60/364,656, filed March
5 14, 2002, entitled ELECTRONIC BATTERY TESTER WITH LOW
TEMPERATURE RATING DETERMINATION; U.S. Serial No.
10/098,741, filed March 14, 2002, entitled METHOD AND
APPARATUS FOR AUDITING A BATTERY TEST; U.S. Serial No.
10/101,543, filed March 19, 2002, entitled ELECTRONIC
10 BATTERY TESTER; U.S. Serial No. 10/112,114, filed March
28, 2002; U.S. Serial No. 10/109,734, filed March 28,
2002; U.S. Serial No. 10/112,105, filed March 28, 2002,
entitled CHARGE CONTROL SYSTEM FOR A VEHICLE BATTERY;
U.S. Serial No. 10/112,998, filed March 29, 2002,
15 entitled BATTERY TESTER WITH BATTERY REPLACEMENT
OUTPUT; U.S. Serial No. 10/119,297, filed April 9,
2002, entitled METHOD AND APPARATUS FOR TESTING CELLS
AND BATTERIES EMBEDDED IN SERIES/PARALLEL SYSTEMS; U.S.
Serial No. 10/128,790, filed April 22, 2002, entitled
20 METHOD OF DISTRIBUTING JUMP-START BOOSTER PACKS; U.S.
Serial No. 60/379,281, filed May 8, 2002, entitled
METHOD FOR DETERMINING BATTERY STATE OF CHARGE; U.S.
Serial No. 10/143,307, filed May 10, 2002, entitled
ELECTRONIC BATTERY TESTER; U.S. Serial No. 60/387,046,
25 filed June 7, 2002, entitled METHOD AND APPARATUS FOR
INCREASING THE LIFE OF A STORAGE BATTERY; U.S. Serial
No. 10/177,635, filed June 21, 2002, entitled BATTERY
CHARGER WITH BOOSTER PACK; U.S. Serial No. 10/207,495,
filed July 29, 2002, entitled KELVIN CLAMP FOR

ELECTRICALLY COUPLING TO A BATTERY CONTACT; U.S. Serial No. 10/200,041, filed July 19, 2002, entitled AUTOMOTIVE VEHICLE ELECTRICAL SYSTEM DIAGNOSTIC DEVICE; U.S. Serial No. 10/217,913, filed August 13, 2002, entitled, BATTERY TEST MODULE; U.S. Serial No. 60/408,542, filed September 5, 2002, entitled BATTERY TEST OUTPUTS ADJUSTED BASED UPON TEMPERATURE; U.S. Serial No. 10/246,439, filed September 18, 2002, entitled BATTERY TESTER UPGRADE USING SOFTWARE KEY; U.S. Serial No. 60/415,399, filed October 2, 2002, entitled QUERY BASED ELECTRONIC BATTERY TESTER; and U.S. Serial No. 10/263,473, filed October 2, 2002, entitled ELECTRONIC BATTERY TESTER WITH RELATIVE TEST OUTPUT; U.S. Serial No. 60/415,796, filed October 3, 2002, entitled QUERY BASED ELECTRONIC BATTERY TESTER; U.S. Serial No. 10/271,342, filed October 15, 2002, entitled IN-VEHICLE BATTERY MONITOR; U.S. Serial No. 10/270,777, filed October 15, 2002, entitled PROGRAMMABLE CURRENT EXCITER FOR MEASURING AC IMMITTANCE OF CELLS AND BATTERIES; U.S. Serial No. 10/310,515, filed December 5, 2002, entitled BATTERY TEST MODULE; U.S. Serial No. 10/310,490, filed December 5, 2002, entitled ELECTRONIC BATTERY TESTER; U.S. Serial No. 10/310,385, filed December 5, 2002, entitled BATTERY TEST MODULE, U.S. Serial No. 60/437,255, filed December 31, 2002, entitled REMAINING TIME PREDICTIONS, U.S. Serial No. 60/437,224, filed December 31, 2002, entitled DISCHARGE VOLTAGE PREDICTIONS, U.S. Serial No. 10/349,053, filed January 22, 2003, entitled APPARATUS

AND METHOD FOR PROTECTING A BATTERY FROM OVERDISCHARGE,
U.S. Serial No. 10/388,855, filed March 14, 2003,
entitled ELECTRONIC BATTERY TESTER WITH BATTERY FAILURE
TEMPERATURE DETERMINATION, U.S. Serial No. 10/396,550,
5 filed March 25, 2003, entitled ELECTRONIC BATTERY
TESTER, U.S. Serial No. 60/467,872, filed May 5, 2003,
entitled METHOD FOR DETERMINING BATTERY STATE OF CHARGE, which
are incorporated herein in their entirety.

There is an ongoing need to improve accuracy
10 in measurements obtained using electronic battery
testers.

SUMMARY OF THE INVENTION

A battery tester cable for coupling an
electronic battery tester to a battery including a
15 first clamp configured to provide a Kelvin connection
to a first electrical terminals of the battery and a
second clamp configured to provide a Kelvin
connection to a second electrical terminals of the
battery. A first cable electrically connects the
20 first clamp to the battery and a second cable
electrically connects the second clamp. A moveable
cable holding device can be positioned along a length
of the first and second cables to thereby secure the
first and second cables together and reduce errors in
25 battery tester measurements due to separation between
the first and second cables. A method is also
provided.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a simplified schematic diagram showing a cable for coupling an electronic battery tester to a storage battery which includes a moveable cable holding device in accordance with the present invention.

Figure 2 is a perspective view showing the battery tester cable of Figure 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 1 is a simplified schematic diagram which shows an electronic battery tester 10 couples to a storage battery 12 through a battery tester cable 14. Electronic battery tester 10 is of the type which determines a condition of battery 12 based upon a dynamic parameter of the battery 12. The dynamic parameter is measured through Kelvin connections to terminals of the battery. The spacing between the cables which couples to the Kelvin connections can be a source of errors in dynamic parameter measurement. This is due to the relatively small signal that is being measured and/or the sensitivity of the test equipment to RF interference, changes in capacitance and inductance as the cables are moved.

Cables 14 include clamps 16 and 18 which provide Kelvin connections to electrical terminals 12A and 12B, respectively. Clamps 16 and 18 are coupled to a first cable 20 and a second cable 22 which extends between clamps 16 and 18 and a connector 24 of electronic battery tester 10. First cable 20 and second cable 22 together make up cable

14. Cables 20 and 22 may be bonded or otherwise coupled together partially along their length as they extend from connector 24. However, cables 20 and 22 separate at some point so that clamps 16 and 18 can
5 be split apart to couple to terminals 12A and 12B of battery 12.

The present invention includes a moveable cable holding device 26 which can be positioned along the link of cable 14 to secure cables 20 and 22
10 together. This divides cable 14 into a length L_1 and L_2 . L_1 is the length along which cables 20 and 22 run together. L_2 is the length over which cables 20 and 22 are split apart. Although this diagram shows the length L_1 over which cable 20 and 22 are separated as
15 being equal, in some embodiments different links are used.

The configuration shown in Figure 1 allows an operator to position the moveable cable holding device 26 in a manner to reduce the length L_2 and
20 increase the length L_1 . This reduces errors in battery tester measurements performed by electronic battery tester 10 due to radio frequency (RF) interference, or changes in capacitance and inductance as the cables 14 are repositioned during the testing
25 procedure. This is required to be different size batteries and battery configurations have different spacings between the terminals. The moveable cable holding device 26 can take any appropriate configuration. For example, the moveable cable

holding device 26 can be a single ring or it can be an elongate sheath which may or may not be expandable along the length of cable 14.

Any number of moveable cable holding devices can be used, as desired, for example Figure 1 shows an optional additional moveable cable holding device 28. The moveable cable holding devices can be configured to slide along the length of cable 14 or, in some embodiments, can be completely removed from cable 14. Example cable holding devices include a ring or a loop which frictionally engages the sides of cable 14 and can slide along cable 14, a flexible loop of material which can be tightened and couple to itself using hook and loop fasteners or other attachment technique, or other configurations.

The electrical connector 24 to electronic battery tester 10 can be a plug or other removable connector, or can be an unremovable connection, for example if the cable wiring is soldered or otherwise permanently attached to electronics within battery tester 10. The cables 20 and 22 each include two individual electrical wires used to provide Kelvin connections. The two individual electrical wires that typically are electrically insulated from each other and carried in an insulating sheath.

Figure 2 is a perspective view showing cable 14 coupled to battery 12. Battery 12 is illustrated as a battery within a bank of batteries configured in a manner used in standby power systems.

Figure 2 shows moveable cable holding device 26 positioned along the length of cable 14 in a manner to reduce the distance over which cable 20 and 22 are separated as they extend from electrical connector 24
5 to battery terminals 12A and 12B. As discussed above, all of this reduces errors in battery tester measurements performed by electronic battery tester 10 shown in Figure 1.

Although the present invention has been
10 described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention. The battery tester can measure a dynamic parameter of
15 the battery using a signal which varies with time. The battery tester can be a stand alone unit or integrated with other equipment such as a battery charger. A moveable cable holding device which can be positioned along a length of the first and second
20 cables to thereby secure the first and second cables, minimizing the separation but allowing for various test terminal spacing, and reduce errors in battery test measurements.